

Full-HD Speed-Dome Camera with IR-LEDs G-Cam/ESD-4630

G-Cam/ESD-4630

The Speed Dome Camera with Full HD resolution and infrared LEDs is suitable for outdoor use even in absolute darkness. With the 360 degree panning and freely controllable lens with a tilt range from -10 to 190 degrees, you have the perfect overview. In addition, 256 fixed positions can be set, which allows a targeted control of certain scenes. With the 40x optical zoom, distant areas will not be unnoticed and can be controlled in the usual high quality.

!! Note: The article is now delivered without audio / analog video !!

Technical Data:

Mega pixel: 1080p (1945 x 1097 eff.)

Image sensor: 1/2,8" Progressive CMOS

Pixel size: 2.9 µm

Lens: 4.3 - 170 mm

Auto focus: Automatic / Manual

Zoom ratio (optical): 40x

Zoom ratio (digital): On/Off; x10

Image Stabilizer: Yes; On/Off

F-Stop: F1.6 (Wide)

Angle of vision: Wide: 66° (H) x 40° (V); Tele: 2° (H) x 1° (V)

Panning range: 360° endless

Tilting range: -20° to +100°

Panning/Tilting speed: 0.1°/s to 90°/s (manual)

Preset speed: 5°/s to 400°/s (pan/tilt)

Preset accuracy: 0.16°

Auto flip / Digital flip: Yes; mechanical, off

Preset positions: 256 positions

Sequence: Yes; 8 x

Cruise: Yes; 8 x

Auto Pan: Yes; 4 x

Servo Feedback: Yes

Video output (stream dependent): Composite video: 1 Vpp, 75 Ohm (BNC)

Minimum sensitivity: 0.02 Lux color; 0.001 Lux BW

Day/Night function: Auto/Light on/Light Off/Day/Night/Light Sensor/Smart

IR-LEDs: yes; distance depends on focal length, 150 m max.

Focus Window: Yes

Wide Dynamic Range: HDR (110 dB max.)

White balance: Auto/ATW/One Push/Manual

Shutter: 1/1 - 1/10,000 s

Back Light compensation: Yes / No

Digitale Noise Reduction: 2D/3D/Color NR

Text overlay: Yes

Interface: 10/100 Mbps Ethernet

Colour / B/W switching: Automatic/Manual (IR-cut filter)

OSD-Menu: English/German/French/Italian/Korean/Simplified Chinese/Traditional Chinese/Russian/Spanish/Japanese/Portuguese

Compression: H.264/H264CCTV, H.265/H265CCTV, MJPEG

Picture rate: H.264/H264CCTV: 1080p @ 30fps + 1080p @ 30fps; H.265/H265CCTV: 1080p @ 30fps + 1080p @ 30fps
Resolutions: 16:9 formats only: 1080p, 720p, 960 x 544, 360p
Video Streaming: Single, Dual, Triple + Quad Stream, configurable
Protocols: HTTP, HTTPS, TCP, FTP, RTSP, RTP, UDP, SMTP, SNMP, ICMP, IGMP, DHCP, UPnP, PPPoE, QoS, NTP, DDNS, ARP, IPv4/v6
Network security: User Authentication, IP-Filter, HTTPS (TLS1.2), IEEE802.1X (SHA-2)
User Account: 20
Browser: Internet Explorer 11 and higher, Chrome, Firefox, Safari
ONVIF compatible: Yes; Profile S, G, Q, T
Motion detection: Yes; 4 zones
Privacy masking: 20 zones, polygons, free scalable, 8 colors
Alarm In/Outputs: 4 In (potential free) / 2 out
Alarm reactions: Preset, Sequence, Auto Pan, Cruise
Home Function: Preset, Sequence, Auto Pan, Cruise
Audio: 1x Line In, 1x Line Out/G.711, G.726, AAC, LPCM
Picture Memory: µSD slot (128 GB max.)
Operating temperature: - 40 °C bis + 50 °C (w/ heater)
Humidity in operation: 10 % to 90 % rel. humidity (non condensing)
Built-in heater / fan: yes / no
Voltage supply: 24 VAC ; HighPoE 60W
Power consumption: 24 VAC/39 W
Zero downtime power switching: Yes; double power supply required
Dimensions in mm (Diameter x H): 207,4 x 300,4 (w/sunshield)
Weight, Housing material and color: Approx. 3,8 kg, Metal/Plastic, RAL 9003
Protective rating: IP 66
Certifications: FCC, CE, RoHS
Licensing: G-Core

Turnkey delivery and installation or turnkey assembly and connection

Model: G-Cam/ESD-4630

Brand: Geutebrück or similar