

## Full-HD Fixdome Camera incl. ceiling installation kit G-Cam/EFD-3131

G-Cam/EFD-3131

High-resolution 1/2.8" CMOS 2-megapixel, 1080p day/night IP-camera with the following features:  
Integrated P-Iris autofocus variable lens F1.3 (zoom and focus can be adjusted with a motor via a browser).

Focal length 3-9mm and digital zoom x2-x16.

Resolution: Pixel (H x V):

1920 (H) x 1080 (V) effective in picture format

16:9, progressive image scanning, built-in IR-LED

lighting (850nm, 8 pcs, 40m range).

Minimum sensitivity (with 2 shutter XWDR):

Color: 0.01 lux; B/W: 0.0005 lux, XWDR/Ultra WDR

120dB, movable IR cut filter, automatic

white balance, automatic exposure control,

backlight compensation and digital

noise reduction and text overlay.

Mirror function and corridor view.

Motion detection, privacy masking and digital

image stabilization.

Compression H.264 and MJPEG. Refresh rate

(full resolution): MJPEG: 30 fps or H.264: 60

fps (not simultaneously!) Resolution 1080p, 720p

and 360p. Configurable QuadStream.

1x audio in, 1x audio out in format G.711 and

G.726. Interface: Via browser.

Protocols: HTTP, HTTPS (TLS 1.2 only metadata),

TCP, FTP, RTSP, RTP, UDP, SMTP, SNMP, ICMP, IGMP,

DHCP, UPnP, PPPoE, QoS, ONVIF, IPv4/v6, IEEE802.1X

(SHA-2). ONVIF protocol: Profile S

Slot for micro  $\mu$ SD card up to 64GB (SD card is not included)

Operating temperature: -30 °C to 50 °C

Power supply: PoE and 12 VDC

Power consumption: Max. 3.64 W

Dimensions in mm (Ø x H): 128.5 x 90mm

Weight: Approx. 405 g

Certification: FCC, CE, RoHS

Software option: G-Core/CamConnect (8.34020)

Is required; connection via E3IPC plug-in.

Accessories: Quick guide, CD

Housing: Plastic (ABS)

Color: Similar to signal white (RAL9003)

Turnkey delivery and installation or turnkey assembly and connection

Typ: G-Cam/EFD-3131

Brand: Geutebrück or similar