

## Day/Night Mini Bullet Camera G-Cam/EWPC-3285

### G-Cam/EWPC-3285

High resolution 1/3"-CMOS 3-Megapixel 1080p Day/Night IP-Bullet camera with Dual-Streaming in H.264 and MJPEG. Additionally the camera offers automatically functions for White Balance, Exposure, Ultra WDR / XWDR < 120dB and Digital Image Stabilization (DIS).

Also included are Text overlay, Motion Detection zones (4 sets of 10 fields), and Privacy Masking (5 zones).

Picture format: 16:9

Scanning system: Progressive Scan

Minimum sensitivity 0,1 Lux (Color), 0.01 Lux (B/W)

Day-/Night-Function: Removable IR-Cut Filter

IR-LEDs: 5 LEDs, 850 nm, 15 m illumination distance

Interface: via Browser

Compression: H.264, MJPEG, ONVIF compatible.

Picture rate (full resolution): H.264: up to 30 fps; MJPEG: up to 30 fps (not concurrent)

Resolution: From 176 x 144 up to 1920 x 1080 Pixel

Lens: Vari-focal lens with focal length from 3.0 to 10.5 mm at F1.6

Manually adjustable focus and zoom

FOV (V): 99,2° (wide) / 31,2° (tele)

Operating temp.: -10 up to 60 °C (@ 10 up to 90 % humidity, non-condensing)

Power supply: 12 VDC / PoE (IEEE 802.3af)

Power consumption: camera 5.3 W + LEDs 1.2 W

Dimensions in mm (Diameter x H): 72 x 150

Connectors: RJ-45 for 10/100/1000 - Base/T Ethernet

12 VDC (3.5 mm plug), Slot for Micro SDHC-card, max. 64 GB (card is not included)

Weight: approx. 330 g

Certifications: CE, FCC, RoHS, IP66

Software Option: G-Core/CamConnect (8.34020) is required; implementation via E3IPC PlugIn.

Housing: Die cast aluminum

Color: Ivory

Turnkey delivery and installation or turnkey assembly and connection

Model: G-Cam/EWPC-3285

Brand: Geutebrück