

## Performance Test

### G-ST 6000+ G3

#### Specifications:

|                     |   |
|---------------------|---|
| Device type:        | G-ST 6000+ G3                                   |
| CPU:                | 12th Gen Intel(R) Core(TM) i7-12700             |
| Mainboard:          | Kontron K3842-Q2                                |
| G-Core:             | 7.2.0.279                                       |
| SSD/ HDD:           | M.2 SSD 256GB ; HDD: 1TB                        |
| Monitor resolution: | 1080p   |
| RAM:                | 1x 16GB DDR5                                    |
| OS:                 | Microsoft Windows 10 Enterprise LTSC (21H2)     |
| Graphiccard:        | Intel(R) UHD Graphics 770 Version 31.0.101.4091 |
| Date of the test:   | 20.04.2023                                      |

#### Results:

##### E4 Viewer Performance:

| Resolution | Codec      | Desired FPS per Channel | Amount Viewers | CPU Usage in % | Device Band-width in Mbit/s | GPU Decoder Usage | GPU 3D Usage |
|------------|------------|-------------------------|----------------|----------------|-----------------------------|-------------------|--------------|
| 4K2K       | H.264 CCTV | 25                      | 12             | 24,31          | 139,32                      | 71,86             | 56,14        |
| 4MP        | H.264      | 25                      | 22             | 27,61          | 228,84                      | 83,83             | 63,83        |
| FullHD     | H.264      | 25                      | 40             | 40,28          | 375,48                      | 99,43             | 84,29        |
| HD         | H.264      | 25                      | 58             | 54,24          | 650,35                      | 66,43             | 94,14        |
| 4MP        | H.265      | 25                      | 22             | 47,28          | 171,77                      | 68,71             | 95,14        |
| FullHD     | H.265      | 25                      | 39             | 52,59          | 261,41                      | 67,71             | 97,43        |
| HD         | H.265      | 25                      | 57             | 54,57          | 519,97                      | 50,86             | 90,86        |

## E4 Database Performance:

| Resolution | Codec      | Recorded Channels | CPU Usage in % | Device Bandwidth in Mbit/s | GPU 3D Usage |
|------------|------------|-------------------|----------------|----------------------------|--------------|
| 4K2K       | H.264 CCTV | 120               | 12,46          | 709,44                     | 4,33         |
| 4MP        | H.264      | 83                | 7,51           | 946,36                     | 4,33         |
| FullHD     | H.264      | 94                | 7,23           | 843,52                     | 4,5          |
| HD         | H.264      | 85                | 8,84           | 949,5                      | 4,33         |
| 4MP        | H.265      | 128               | 6,32           | 228,54                     | 4,5          |
| FullHD     | H.265      | 128               | 6,76           | 197,93                     | 4,75         |
| HD         | H.265      | 128               | 6,73           | 246,06                     | 4,5          |

## E4 G-Tect Performance AD:

| Resolution | Codec      | Analysed Channels AD | CPU usage in % AD | Device Bandwidth in Mbit/s AD | GPU Decoder Usage AD | GPU 3D Usage AD |
|------------|------------|----------------------|-------------------|-------------------------------|----------------------|-----------------|
| 4K2K       | H.264 CCTV | 54                   | 42,01             | 501,46                        | 84,27                | 59              |
| 4MP        | H.264      | 33                   | 20,95             | 372,03                        | 96,91                | 53,73           |
| FullHD     | H.264      | 60                   | 26,03             | 646,9                         | 99,36                | 59              |
| HD         | H.264      | 84                   | 30,47             | 909,75                        | 67,18                | 51,09           |
| 4MP        | H.265      | 40                   | 38,31             | 338,62                        | 96,82                | 95,09           |
| FullHD     | H.265      | 66                   | 48,98             | 468,41                        | 87,36                | 93,36           |
| HD         | H.265      | 84                   | 38,23             | 808,49                        | 63,64                | 56,09           |

## E4 G-Tect Performance VMD:

| Resolution | Codec      | Analysed Channels VMD | CPU usage in % VMD | Device Bandwidth in Mbit/s VMD | GPU Decoder Usage VMD | GPU 3D Usage VMD |
|------------|------------|-----------------------|--------------------|--------------------------------|-----------------------|------------------|
| 4K2K       | H.264 CCTV | 39                    | 31,37              | 609,34                         | 88,18                 | 60,91            |
| 4MP        | H.264      | 34                    | 20                 | 369,74                         | 99,91                 | 53,73            |
| FullHD     | H.264      | 60                    | 26                 | 640,55                         | 98,91                 | 59,09            |
| HD         | H.264      | 84                    | 28,85              | 948,63                         | 68,45                 | 49,55            |
| 4MP        | H.265      | 40                    | 37,22              | 365,21                         | 99,45                 | 96,91            |
| FullHD     | H.265      | 67                    | 44,67              | 471,15                         | 86,82                 | 91,82            |
| HD         | H.265      | 82                    | 36,7               | 791,18                         | 65                    | 57,91            |

## E4 G-Tect Performance VMX:

| Resolution | Codec      | Analysed Channels VMX | CPU usage in % VMX | Device Bandwidth in Mbit/s VMX | GPU Decoder Usage VMX | GPU 3D Usage VMX |
|------------|------------|-----------------------|--------------------|--------------------------------|-----------------------|------------------|
| 4K2K       | H.264 CCTV | 43                    | 22,08              | 451,21                         | 100                   | 58,45            |
| 4MP        | H.264      | 31                    | 24,89              | 339,19                         | 99,73                 | 54,36            |
| FullHD     | H.264      | 51                    | 34,77              | 538,25                         | 97,82                 | 59,27            |
| HD         | H.264      | 83                    | 54,93              | 950,7                          | 95,27                 | 68,55            |
| 4MP        | H.265      | 31                    | 49,28              | 259,68                         | 88,73                 | 91,27            |
| FullHD     | H.265      | 51                    | 60,3               | 350,98                         | 80,64                 | 90,18            |
| HD         | H.265      | 76                    | 83,9               | 732,93                         | 81,3                  | 79,8             |

### **Type:** Limit Performance Test

**Reason:** Search for the limits of the device until the expected frame rate is no longer reached. Live streams from GBF reference files are used.

**Test definition:** Tested in a separate test environment with separate network and imagesource with new GBF reference files.

**Aim:** Determine the maximum number of cameras that can be displayed live, being recorded in the database or analyzed with the G-Tect service (AD, VMD, VMX) WITHOUT database storage.

**Description:** SuT-Limit Test; In this test case, the maximum number of channels per device is searched for. It is determined how many channels can be viewed live and how many channels can be recorded.

All tests are performed exclusively at 25 FPS, since it was found in comparison tests that the system behaves as follows when the frame rate is halved:

- GView: at 12.5 FPS always double the number of channels
- Database: at 12.5 FPS always double the number of channels
- GTect: with AD and VMD at 12.5 FPS always double the number of channels
- GTect: with AD and VMX always 8 images are analyzed with CCTV → same number of channels
- GTect: with AD and VMX always 8 images are analyzed with CCTV → same number of channels

For GView and G-Tect, only the "Outdoor Lively" scenario was used because it is the most complex and the smallest number of channels could be connected or analyzed.

**Procedure:**

**GView:** The program starts with 16 channels. If the expected frame rate is reached, another 16 channels are activated. This happens as long as the frame rate is reached.

If this is no longer the case, 8 channels are deleted again. If this is reached, 4 more channels are switched on again and so on. This happens until the maximum frame rate is reached.

**Database:** It starts with 128 active channels. If the frame rate is reached, another 64 channels are activated in the setup. If the rate for all 192 channels is then reached the test is finished.

If the frame rate for the 192 channels is not reached, 32 channels are deactivated again, and soon.

**G-Tect:** AD, VMD and VMX are tested separately. No combination is used.

The program starts with 16 active channels. When the expected frame rate is reached, another 16 channels are activated. This happens as long as the frame rate is reached.

If this is no longer the case, 8 channels are deactivated. If this is reached, 4 more channels are activated again and so on. This happens until the maximum frame rate is reached.

A comparison of the G-Tect performance tests with active recording with the results without recording has shown that this has no effect on the performance of the G-Tect service.

Therefore, no recording is active in this test.