

Camera for Automatic Number Plate Recognition G-Cam/ANPR-4901 12-50mm



- Optimal camera/lens combination for best recognition results either day or night.
- Minimized distortions from surrounding lights or from vehicle headlights.
- Sharp pictures also with fast moving vehicles due to short exposure times.
- Mainly pre-configured for quick installation.
- Eye protection rating according to VDE 0837, DIN EN 60825-1 standards, 3A rating

Complete set for reliable day and night license plate recognition, including camera, lens, weatherproof housing, IR-Pass filter and IR headlight. The entire system was specially designed and developed for use in conjunction with the Geutebrück ANPR / LPR analysis software

- Access barriers to multi-storey car parks.
- Documentation of the time trucks stay on the company premises.
- Complete yard management in conjunction with the Vehicle Access Manager.
- Automatic barrier management based on the license plate.

Technical data

| | |
|--------------------------------|--|
| Mechanical | Weatherproof housing, wall mount bracket cable managed, IR-pass filter, splitter, camera, lens |
| Dimension mm | Housing: 470x165x122 - Illumination: 128x178x62 |
| Weight | Approx. 5 kg |
| Housing | Body: Aluminum - Sunshield: Plastic |
| Color | RAL 7035 light grey |
| Voltage supply | PoE+ / IEEE802.3 at |
| IP class | IP 66 |
| Operating Temperature | -20° - +50° |
| Lens | 12-50mm |
| Angle of view | Wide: 792° (H) x 43,9° (V) Tele: 25,1° (H) x 14,8° (V) |
| IR Illumination Distance | Yes |
| Max. Radiation Angle (adaptiv) | 30° |
| Wavelength | 850nm |
| Max. Range | 130 m |
| Fan | No |
| Optional accessories | G-Case/PMA-040 (5.18377) pole mount adapter with tightening strap |
| Application area | Outdoor |
| Brand | Geutebrück |
| Order No. | 0.02492 |