

GEUTEBRÜCK

VIDEO MANAGEMENT

SECURITY MANAGEMENT

VIDEO CONTENT ANALYSIS

INTEGRATION AND MONITORING

SERVICE

HARDWARE

Hardware platform for Geutebrück software solutions G-ST 6000+ G3



MADE
IN
GERMANY



- Microsoft Windows 11 IoT Enterprise LTSC
- Powered by Intel 12gen. IoT
- Up to 64GB DDR5 RAM for even more performance
- Available RAID level 0,1,5,6
- Up to 160TB with 8x 3,5"-HDD storage bays, hot swapable

Contact us for additional details on bundled options or to place an order.

The 19" rack mounted hardware platform ensures optimum interaction with Geutebrück software. Can be used as a stand-alone unit for a medium to large video management system with higher storage requirements or, for use in a networked solution across multiple branches or facilities. Also suitable as an all-in-one VMS solution for larger video systems such as education, corrections, healthcare, law enforcement, logistics and many more. Analog kit options allow the unit to be converted into a hybrid VMS.

- Designed to meet the demanding requirements of processing a wide range of video content analysis with G-Core or as a separate Analytics server
- Hot-swappable power supplies and mirrored SSDs for the operating system are features that enhance redundancy

Technical data

Software

Operating System: Windows 10 IoT Enterprise LTSC Windows 11 IoT Enterprise LTSC	G-Core: 6.2, 7.1 or newer with GPU support	G-SIM: 9.4.3, 10.0.1 or later with GPU support
--	--	--

Performance*

Record: 750 Mbit/s database; 92 channels	Viewer: 360 Mbit/s; 38 channels	G-Tect: AD: 58 channels, VMD: 58 channels, VMX: 50 channels
--	---	--

Memory

System: 1x M.2 SSD (opt. 2x M.2 SSD Raid1)	Image memory: up to 8x HDD, hot swap, Raid 0,1,5,6 (max. 160TB)
--	--

System

Processor: Intel Core i5 or i7 12th gen. IoT	Memory RAM: 16GB DDR5 Single Dual Channel (opt. 64GB)	Video outputs: 4x DisplayPort V1.4a, 4K Resolution
Audio output: 1x stereo (line out, phone jack 3.5mm), display port	USB: Rear: 4x USB 3.2 (Gen1) Type A, 2x USB 3.2 (Gen2) Type A, 1 x USB 3.2 (Gen2) Type C Front: 2 x USB 2.0 Typ A	Network interfaces: 1x Port 10/100/1000 MBit/s base-TX iAMT 1x Port 10/100/1000/2500 MBit/s
Other interfaces: 1x RS232 16x input contacts, sabotage monitored 8x potential free relay outputs, 24VDC 1A	Power supply: Redundant: 100-240V AC / 60-50 Hz ±10%, 2x 420W Hot-Swap	Power consumption: ca. 185W (1x M.2 SSD, 8x HDD Raid 5)

Environment

Operating temperature: 0°C to +40°C	Form factor: 3U / 3HE	Dimensions: 19" rack mount unit: 3 U x 542 mm (depth); 482 x 133 x 542 mm (W x H x D)
---	---------------------------------	--

Certifications

CE, EAC

Warranty

3 years (opt. 5 years)

Accessories

System memory: 0.08060 M.2 SSD mirrored, Raid 1	Image storage: up to 8x HDD, hot swap, Raid 0,1,5,6	Network interfaces: 5.35466 1 Port Gbit network card PCIe 5.35465 2 Port Gbit network card PCIe
Memory RAM: 1.02921 16GB RAM Kit (max. 64GB)		Analog-Kit: (Win10 only) 1.02460 Analog-Kit H8 1.02470 Analog-Kit H16

*Configuration: G-ST 6000+G3 with i7 and 16 GB RAM Video source: Scene OutdoorLively, 25fps, H.264, FullHD. Each test was performed separately. In combination the values are lower.

Order no. 0.60620