## GEUTEBRÜCK

VIDEO MANAGEMENT

SECURITY MANAGEMENT

VIDEO CONTENT ANALYSIS

INTEGRATION AND MONITORING

IG SERVICE

HARDWAR

## Special hardware for Perimeter+ application G-ST Perimeter+ G3

		0
	© GEUTEBRÜCK	
1		
		0

The special Perimeter+ hardware in desktop design ensures an optimal interaction with the Geutebrück Perimeter+ software. Ideal as a stand alone device for a medium sized perimeter protection system up to 16 channels.

- Suitable for perimeter protection systems (up to 16 cameras), e.g. for bank branches, schools, industrial facilities, critical infrastructure, gas stations.
- Suitable for higher video content analysis requirements or higher quality video images.
- Built for Geutebrück Perimeter+ solutions.

## Please contact a sales representative for pricing information, configuration options and ordering.

- Our standard device for Perimeter+ applications
- Powered by Intel 12gen.
  IoT
- Perfectly adapted to the requirements of perimeter protection.
- Ideal for running 16 channels of Perimeter+ analysis.
- With 16 GB RAM for even more analysis power!
- Higher reliability due to the choice of an industrial component.
- Also suitable for installation in server cabinets

## Technical data

Software				
Operating System: Windows 11 IoT Enterprise LTSC				
Performance*				
Record: N/A	Viewer: N/A	<b>G-Tect:</b> Perimeter+: 16 Channels or Perimeter+ ALR: Channels		
Memory				
<b>System:</b> 1x M.2 SSD	Image memory: N/A			
System				
Processor: Intel Core i5 12th gen. IoT	Memory RAM: 16GB DDR5 Single Dual Channel	<b>Video outputs:</b> 4x DisplayPort VI.4a		
<b>Audio output:</b> 1x stereo (line out, phone jack 3.5mm), display port	USB: Rear: 4x USB 3.2 (Gen1) Type A, 2x USB 3.2 (Gen2) Type A, 1 x USB 3.2 (Gen2) Type C Front: 2 x USB 2.0 Typ A	Network interfaces: 1x Port 10/100/1000 MBit/s base-TX iAMT 1x Port 10/100/1000/2500 MBit/s		
Other interfaces: 1x RS232	<b>Power supply:</b> 100-240V AC / 60-50 Hz ±10%, 300W	Power consumption: approx. 140W (1x SSD, 1x HDD)		
Environment				
<b>Operating temperature:</b> max. 2x HDD 0°C to +40°C <b>Weight:</b> approx. 11.6 kg net	Form factor: 3U / 3HE	<b>Dimensions:</b> 19" rack mount unit: 3 U x 415 mm (depth); desktop unit: 443 x 140 x 436 mm (W x H x D) incl. base and front cover		
Certifications				
CE, EAC				
Warranty				
3 years (opt. 5 years)				
Accessories				
System memory: N/A	Image storage: N/A	Network interfaces: N/A		
<b>Memory RAM:</b> 1.02921   16GB RAM Kit (max. 64GB)	Rackmount: 4.21744   19" Rackmount Kit	Analog-Kit: N/A		
*Configuration: G-ST Perimeter+G3 with i5 and 16 GB RAM Video source: Perimeter+ Performance Test Tool.				

\*Configuration: G-ST Perimeter+G3 with 15 and 16 GB RAM Video source: Perimeter+ Performance Te Each test was performed separately. The values are lower in combination.

Order no. 0.60360