

## Hardware platform for Geutebrück software solutions G-ST 800



The short SFF hardware platform ensures optimal interaction with the Geutebrück software. Can be used as a standalone video management system unit or in a network solution for multiple stores or facilities. Also suitable as an all-in-one VMS solution for small video systems.

- Optimized for small projects with up to 20 cameras, such as post offices, petrol stations, warehouses, etc.
- Small Desktop Case due to the highly minimized design
- Protection of the building against intrusion by unauthorized persons
- Ideal for use as a ViewStation in larger video management systems using GView or G-SIM OpCon
- Suitable for high video quality requirements

- Microsoft Windows 11 IoT Enterprise LTSC
- Powered by Intel 12gen. IoT
- 16 GB DDR5 RAM for even more performance
- Up to 8TB with 3,5"-HDD storage bay
- S.F.F. Desktop Case 330 x 96 x 411 mm

**Please contact a sales representative for pricing information, configuration options and ordering.**

# Technical Data

## Software

<b>Operating System:</b> Windows 11 IoT Enterprise LTSC	<b>G-Core:</b> 8.1 or newer with GPU support	<b>G-SIM:</b> 10.0.2, 11.0 or later with GPU support
--	---	---

## Performance\*

<b>Record:</b> 560 Mbit/s database; 20 channels*	<b>Viewer:</b> Viewer: 280 Mbit/s; 36 channels*	<b>G-Tect:</b> AD: 36 channels, VMD: 35 channels, VMX: 36 channels
---	--	--

## Memory

<b>System:</b> 1x 256GB M.2 SSD	<b>Image memory:</b> 1x HDD (max. 8TB)
------------------------------------	---

## System

<b>Processor:</b> Intel Core i3-12100 12th gen. IoT	<b>Memory RAM:</b> 16GB DDR5 dual channel	<b>Video outputs:</b> 4x DisplayPort V1.4a (Recommended use: max.2)
--	--	---

<b>Audio output:</b> 1x stereo (line out, phone jack 3.5mm), display port	<b>USB:</b> 2x USB 3.2(Gen2) TypeA, 2x USB 3.2(Gen1) TypeA, 2x USB 2.0	<b>Network interfaces:</b> 10/100/1000 MBit/s base-TX
---	---	--

<b>Other interfaces:</b>	<b>Power supply:</b> 110 - 240 V AC / 60 - 50 Hz ±10%, 300W	<b>Power consumption:</b> approx. 80W
--------------------------	--	--

## Environment

<b>Operating temperature:</b> 5°C to +35°C	<b>Form factor:</b> S.F.F.	<b>Dimensions:</b> 330 x 96 x 411 mm
<b>Weight:</b> Approx. 7.0 kg net		

## Certifications

CE

## Warranty

3 years (opt. 5 years)

## Accessories

**Network interfaces**  
5.35466 | 1 Port Gbit network card PCIe  
5.35465 | 2 Port Gbit network card PCIe

\*Configuration: G-ST 800 Video source: Scene OutdoorLively, 25fps, H.264, FullHD. Each test was performed separately. In combination the values are lower.

Order no. 0.60083