

## Day/Night Mini Bullet Camera G-Cam/EWPC-3285



- Full HD 1080p resolution up to 30 fps in H.264
- CMOS sensor with progressive scan and Ultra WDR / XWDR < 120 dB
- True Day/Night mode (Retractable IR cut filter) plus IR illumination
- Camera in weatherproof housing with integrated wall bracket (IP66)
- PoE (IEEE 802.3af) supplying possible
- 2.7-12 mm zoom/focus lens manually adjustable
- Cost saving installation and servicing

**Info! New discount group: D**

The IP camera G-Cam/EWPC-3285 is ideal for use in garages, freight forwarders or production halls

The IP camera G-Cam/EWPC-3285 is ideal for use in garages, freight forwarders or production halls. Thanks to switching between day/night and integrated invisible wide-range IR lighting, the camera offers an enormous energy-saving potential. The varifocal lens provides a clear view even for larger areas up to 15 meters without additional lighting. Thanks to the Wide Dynamic Range function, it can clearly display objects in very dark and very light areas of the image. Important areas of the image can even be displayed more clearly in strong, glaring light.

# Technical data

Mega pixel	3 MP
Image sensor	1/3" Sony CMOS
Picture Format	16:9
Lens	f = 2.7 mm to 12 mm (variable)
Lens mounting	CS-Mount
Digital zoom	x2 - x10
F-Stop	F1.6
Angle of view	f = 2.7 mm / 99,2°, f = 12 mm / 31,2°
Minimum sensitivity	0.1 Lux (color) 0.01 Lux (B/W)
Day/Night function	Auto / on / off / smart / day / night / light sensor
IR-LED	850 nm / 15 m
Wide Dynamic Range	WDR (120 dB)
White balance	ATW, One Push, Manual, AWB
Exposure	Automatic / Manual
Shutter	1/1.5 - 1/425 s
Digital Noise Reduction	2D/3D (low/middle/high/off)
OSD Menu	English, German, French, Italian, Korean, Simplified Chinese, Traditional Chinese, Russian, Spanish, Japanese, Portugese
Image rotation	Mirror
Compression	H.264, MJPEG
Protocols	HTTP, HTTPS (TLS 1.2 Metadata only), TCP, FTP, RTSP, RTP, UDP, SMTP, SNMP, ICMP, IGMP, DHCP, UPnP, PPPoE, UPnP, QoS, ONVIF, IPv4/v6, IEEE802.1X (SHA-2)
Browser	Internet Explorer 6.0 and higher, Chrome, Firefox, Safari
Privacy masking	5 Zones
Audio	Line-in, Mic-in, Line-out, G.711, G.726, AAC, LPCM, Built-in Microphone
Operating Temperature	- 20 °C to + 60 °C
Humidity in operation	10 - 90 % rel. humidity (non condensing)
Heater	No
Fan	No
Connectors	RJ-45 for 10/100/1000 - Base/T Ethernet; plug for external power supp
Voltage supply	12 VDC or PoE (IEEE 802.3af)
Power Consumption	5.3 W + 1.2 W IR LEDs
IP class	IP 66
Certification	FCC, CE, EMC, LVD, RoHS
Licensing	unit dependent (Gsc or G-Core)
Dimensions mm (L x B x H)	86 x 151
Brand	Geutebrück
Order No.	5.02601